

CAM-PT-624-B

Black Indoor Pan and Tilt Camera

Night Owl's CAM-PT-624-B is a hi-resolution Pan & Tilt camera (600 TVL) that easily connects to all Night Owl DVR systems.

When connected to a DVR the camera's pan and tilt functions can be controlled remotely from the Internet or from compatible Smartphones and Tablet PCs. Away from your office but need to pan a camera between different employee desks? You can do that remotely, from your phone or tablet. See something suspicious at home but it moves out of the camera range? You can pan or tilt the camera view as needed, from any remote location.

The CAM-PT-624-B is also Night Vision ready, allowing you to see in complete darkness from over 50 feet away.

Key Features

- Indoor Pan & Tilt Camera (Black)
- 600 TV Lines Resolution
- 50 Feet Night Vision
- 100 Feet Easy Connect Video/Power/PT Cable
- Easy to Install Ceiling Mounting Bracket
- 1 Year Warranty
- Compatible With all Night Owl Systems
- 24/7 Technical Phone Support (English & Spanish)
- 24/7 Web Support at www.NightOwlSP.com

Customer Support

24/7, 365 Days a Year

All Night Owl security products come with full technical support, 24/7, 365 days a year (including iChat support* and a Bilingual Help Desk). If needed, our Help Desk will also remotely access your DVR for setup assistance.

Package Contents

- 1 x Camera with Bracket
- 1 x 100 FT BNC/RS485 Cable
- 3 x Mounting Hardware and Screws
- 1 x Installation Guide (English and Spanish)
- 1 x Camera Power Adapter
- 1 x BNC to RCA (Male) Connector
- 3 x Night Owl Security Stickers
- 1x Screw Driver

Camera Specifications

| | |
|---------------------------------------|--------------------|
| Image Sensor | CMOS |
| Sensor Size | 1/3" |
| TV Lines of Resolution | 600 |
| Number of Leds | 24 |
| IR Cut Filter | Yes |
| Backlight Compensation | Auto |
| Effective Pixels | 720*480 |
| Lens mm | 6mm |
| Viewing Angle | 60° |
| Length of Night Vision ⁽¹⁾ | 50 FT |
| Audio ⁽³⁾ | No |
| Length of Cable | 100 FT |
| Type of Cable | Power/Video/RS485 |
| Connection Type | RCA/BNC/RS485 |
| Weatherproof Rating ⁽²⁾ | Indoor Use Only |
| Signal | NTSC |
| S/N Ratio | >48DB |
| Minimum Illumination | 0 Lux (IR On) |
| Power Consumption Per Camera | 800mA |
| Power Supply | DC12V, 1000mA |
| Volts | 110/220V |
| Operating Temperatures (F) | (-14 to 122)F |
| Dimensions | 5.5" x 5.5" x 5.8" |

Other Information:

| | |
|--------------------------|--------------------------------|
| Model Number: | CAM-PT-624-B |
| UPC: | 8-55830-00385-7 |
| Sell Package Dimensions: | 8.66" x 6.89" x 9.45"—4.5lbs |
| Master Pack UPC: | 508-55830-00385-2 |
| Master Pack Quantity: | 4 |
| Master Pack Dimensions: | 17.91" x 14.96" x 10.63"—18lbs |

*iChat support available starting November, 2013.

- (1) Night vision range up to 50 FT under ideal conditions. Objects at or beyond this range may be partially or completely obscured, depending on the camera position.
- (2) Cameras are not recommended for use in temperatures below -14°F or above 122°F. Not waterproof, for indoor use only.
- (3) One audio camera is included.
- (4) Smartphone capable; Night Owl H.264 DVR needed to support pan and tilt functions. See Smartphone compatibility list for your Night Owl analog DVR.

Disclaimer:

Certain uses, publication and/or distribution of video/audio recordings from security cameras and/or audio devices are prohibited or restricted by federal, state and local laws.

When enabling and/or using audio recording features with your hidden security camera, be sure to comply with the laws in your country, state and locality.